

Options and Accessories



Lighting Package\*



Plastic Canopy Top



Custom Van Box



Rear Cargo Cage



Electric Bed Lift




Underhood Storage  
(Gas Only)



Stake-Side Kit



2-Inch Front  
Receiver Hitch



Cargo Bed Toolbox



2,500 lb Warn Winch



Pintle Hitch



Cab Heater



Nerf Bars



62-Inch Plow Blade



60-Inch finish  
cut mower



Swisher Dump Cart



40-Gallon Sprayer



Front Steel  
Skid Plate



Roof-mounted  
Strobe Light



5-Panel Mirror

\*Includes horn, turn signals and brakelights

Club Car supports only the safe and legal use of our products. To reduce the risk of injury, always operate and travel within these vehicles in a safe, lawful and conscientious manner. The vehicles referenced herein are designed and manufactured for off-road use only. As such, they do not conform to Federal Motor Vehicle Safety Standards for automobiles or Low Speed on-road motor Vehicles. For further information on these products (including a full description of the Limited Warranty), please review the applicable owner's manual or contact Club Car, Inc.

Club Car

CARRYALL 295  
UTILITY VEHICLE



Ingersoll Rand is a global diversified firm providing products, services and solutions to enhance the quality and comfort of air in homes and buildings, transport and protect food and perishables, secure homes and commercial properties, and increase industrial productivity and efficiency. Driven by a 100-year-old tradition of technological innovation, we enable our customers to create progress and a positive impact in their world.

1.800.CLUBCAR • +1 706.863.3000

www.clubcar.com www.ingersollrand.com



# CARRYALL 295

Look no further for the industry's first fully automatic 4x4 utility vehicle. Club Car's revolutionary IntelliTrak™ 4-wheel-drive system constantly senses the driving environment and instantly engages and disengages 4-wheel-drive operation as the surroundings change. With nothing to engage, shift or lock, you get a 4x4 that's easy for your whole team to drive. With unique comfort features and durable construction, the Carryall 295 means serious business anywhere you put it to work.




## Features

IntelliTrak™:  
An automatic full-time,  
All-Wheel-Drive system



23 hp air-cooled Kawasaki®  
gas or 20 hp liquid-cooled  
Kubota® diesel engine



Standard Color:  
Dark Gray



Optional Color:  
Green



Camouflage



Roll Over Protective  
Structure certified  
to meet 5 different  
international  
standards



Rustproof, non-corrosive,  
box tube 6061 aircraft-grade  
aluminum frame, chassis  
and cargo box



15.1 ft³ (0.4 m³)  
Cargo Box carries  
800 lb (362.9 kg)



Four-wheel,  
hydraulic  
disc brakes



Double A-Arm  
front suspension  
w/coil-over shocks

## Additional Features

- **Maximum speed of 25 mph (40.2 kph)**
- **1,200 lb (544.3 kg) total vehicle capacity; High Capacity option: 1,450 lb (657.7 kg)**
- **Maximum hp @ 3,600 rpm exceeds SAE J1940/1349 Performance Standards**
- **12.1 in (30.7 cm) ground clearance under foot platform to handle rough terrain**
- **25" heavy-duty, all-terrain tire standard; 25" heavy-duty, mud tire optional**

## Specifications

		Carryall 295 Gasoline	Carryall 295 Diesel
POWER SUPPLY	Engine	Kawasaki, 675 cc, 2-cylinder, industrial grade	Kubota D722, 719 cc, 3-cylinder
	Engine – Cooling	Air	Liquid
	Engine – Lubrication & Oil Filter Type	Full-pressure spin-on	Full-pressure spin-on
	Max Torque	39.8 ft-lb (54 Nm)	33 ft-lb (44.7 Nm)
	Horsepower	23 (17.2 kw) @ 3,600 rpm per SAE J1940/1349	20 (14.9 kw)
	Ignition	Transistorized magneto	Compression
	4WD Engagement	Automatic – IntelliTrak	Automatic – IntelliTrak
	Differential – Front	Automatic – IntelliTrak	Automatic – IntelliTrak
	Differential – Rear	Auto locking – IntelliTrak	Auto locking – IntelliTrak
	Electrical System	12-volt, 500 CCA	12-volt, 500 CCA
STEERING/ SUSPENSION	Torque Converter	CVT	CVT
	Steering Type	Rack & pinion	Rack & pinion
	Tilt Steering Wheel	Standard	Standard
	Adjustable Driver's Seat	Only available with bucket seat option	Only available with bucket seat option
	Suspension – Front	Independent double A-arms w/coil-over shocks	Independent double A-arms w/coil-over shocks
	Suspension – Rear	Swing arm w/coil-over shocks	Swing arm w/coil-over shocks
	Brakes	Four-wheel, hydraulic disc	Four-wheel, hydraulic disc
FRAME/CHASSIS	Park Brake	Automotive style	Automotive style
	Frame/Chassis	Tubular aluminum	Tubular aluminum
	Body – Front	GE Gelay High-impact, scratch-resistant, injection molded color	GE Gelay High-impact, scratch-resistant, injection molded color
	Body – Rear	All aluminum cargo bed	All aluminum cargo bed
	Tires – Front	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)
	Tires – Rear	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)
DIMENSIONS	Instrumentation	Electronic fuel gauge/hour meter, low oil warning light (speedometer optional)	Electronic fuel gauge/hour meter, low oil warning light, coolant high temp warning light (speedometer optional)
	Bed Length x Width x Height	48.8" x 49.8" x 10.9" (124 cm x 126.5 cm x 27.7 cm)	48.8" x 49.8" x 10.9" (124 cm x 126.5 cm x 27.7 cm)
	Overall Bed Height	33" (83.8 cm)	33" (83.8 cm)
	Bed Load Capacity	800 lb (362.9 kg)*	800 lb (362.9 kg)*
	Total Vehicle Capacity	1,200 lb (544.3 kg)**	1,200 lb (544.3 kg)**
	Fuel Tank Capacity	6.5 gal (24.6 L)	6.5 gal (24.6 L)
	Overall Length x Width x Height	124.6" x 60" x 78.6" (316.5 cm x 152.4 cm x 199.6 cm)	124.6" x 60" x 78.6" (316.5 cm x 152.4 cm x 199.6 cm)
	Wheelbase	88.7" (225.3 cm)	88.7" (225.3 cm)
	Ground Clearance – Differential	7.4" (18.8 cm)	7.4" (18.8 cm)
	Tread Centers (Front/Rear)	48.8" (124 cm) front and rear	48.8" (124 cm) front and rear
	Dry Weight (Less Batteries)	1,339 lb (599 kg)	1,475 lb (669.1 kg)
	Maximum Speed	25 mph (40.2 kph)	25 mph (40.2 kph)
	Turning Radius	11.5 ft (3.5 m)	11.5 ft (3.5 m)
	Vehicle Warranty	2-year/2,000-hour, limited	2-year/2,000-hour, limited

\*1,050 lb (476.3 kg) available \*\*1,450 lb (657.7 kg) available