

Options and Accessories



Turn Signals



Locking Glove Box



Heavy-Duty Bumper/
West Coast Mirror



Wheel Covers



Heavy-Duty
Batteries



Battery Capacity
Indicator



Certified ROPS
Cab Enclosure



Fuel Gauge
and Hour Meter



Custom Van Box



Canopy Top
White



Electric Bed Lift



Fold-Down
Windshield



Trailer Hitch



Safety Strobe Light



2-Inch Rear
Receiver Hitch



Pintle Hitch



Cab Heater



Swisher Dump Cart



Toolbox



Stake-Side Kit

Value Packages	Heavy-Duty Bumper	Headlights	Trailer Hitch	Hour Meter*	Differential Guard	Radio/Beverage Holder	Cargo Box**	Extra-Traction Rear Tires	8.5-Inch Premium Tread Front Tires
Carryall 6 Electric	Standard	Standard	✓	✓	✓	✓	✓	✓	✓
Carryall 6 Gasoline	Standard	Standard	✓	Standard	✓	✓	✓	✓	✓

*Fuel Gauge/Hour Meter is standard on all gas vehicles listed.
**Priced separately from base vehicle.



Ingersoll Rand is a world leader in the field of compact vehicles and equipment. Our widely known Bobcat® brand includes an extensive line of powerful, nimble compact construction equipment and attachments, and our state-of-the-art engineering capabilities and stylish designs are reflected in our world famous Club Car® vehicles.

1.800.ClubCar • +1 706.863.3000

www.clubcar.com www.bobcat.com www.ingersollrand.com

CCN 18033043 Rev 08/06

Club Car

CARRYALL 6
UTILITY VEHICLE





Stepping up with more load capacity and amenities, the Carryall 6 enables you to expand your hauling capabilities and handle awkward-sized items with ease. With a cargo bed almost 6 feet long, you'll be sure to have an ample amount of cargo space –



helping you get your job done more efficiently. The Carryall 6 comes with standard headlights, taillights and a horn, features you'll find very beneficial.



Features

Club Car's exclusive IQ Plus System™ electric or 11.5 hp gas engine



Large cargo bed capacity, nearly 6 ft (179.1 cm) long



Rugged, rustproof aluminum frame, chassis and cargo box



Self-adjusting rack & pinion steering




ArmorFlex® front body for fade-resistant color



Standard Color: Dark Gray



Optional Colors: Beige Gray, Green, White, Classic Blue, Red, Black and Burgundy



6-ply, premium tread tires



Smooth, independent front and semi-independent rear suspension

Additional Features

- Maximum speed of 17 mph (27.3 kph) (Electric vehicles only)
- 1,500 lb (681 kg) total vehicle capacity
- 11.5 hp @ 3,600 rpm exceeds SAE J1940 Performance Standards
- Reconfigured dash
- Side fuel fill
- Redesigned hip restraint for maximum styling and comfort
- Headlights, taillights, brakelights and horn
- 4-wheel, mechanical drum brakes

Specifications

		Carryall 6 Electric <small>with exclusive IQ Plus System</small>	Carryall 6 Gasoline
POWER SUPPLY	Engine	N/A	Kawasaki 4-cycle, OHV, 351 cc, single cylinder, air-cooled, pressure-lubricated, spin-on oil filter
	Drive Motor	48-volt Shunt/Sepex	N/A
	Horsepower	3.7 @ 3400 rpm (continuous) 21.0 @ 2000 rpm (peak)	11.5**
	Governor	N/A	Automatic ground speed sensing, internally geared-in unitized transaxle
	Governed RPM	N/A	3050±30
	Ignition	N/A	Electronic w/electronic RPM limiter
	Drive Unit	12.3:1 direct-drive axle, double-reduction helical gear	Unitized transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
	Electrical System	48-volt	12-volt, 500 cca 105 min. reserve
	Batteries	Eight 6-volt, Standard:T105 = 115 min @ 75 amps; Heavy Duty:T145 = 145 min @ 75amps	N/A
	Charger	Onboard with reel, automatic, computer-controlled 48-volt DC, 17 amp, UL and CUL listed; International CE marked available	N/A
STEERING/ SUSPENSION	Controller	500 amp Solid State	N/A
	Steering	Self-adjusting rack & pinion	Self-adjusting rack & pinion
	Front Suspension	Independent leaf spring w/dual hydraulic shocks	Independent leaf spring w/dual hydraulic shocks
	Rear Suspension	Leaf springs w/dual hydraulic shocks	Leaf springs w/dual hydraulic shocks
	Brakes	Four-wheel mechanical drum	Four-wheel mechanical drum
	Park Brake	Foot-operated, multi-lock	Foot-operated, multi-lock
	Stabilizer Bar	No	Yes
FRAME/CHASSIS	Frame/Chassis	Aluminum I-Beam	Aluminum I-Beam
	Front Body	ArmorFlex®	ArmorFlex®
	Rear Body	All aluminum	All aluminum
	Body Finish	Matching paint over molded-in color	Matching paint over molded-in color
	Light Package	Std. light package	Std. light package
	Trailer Hitch	Optional	Optional
	Front Tires	18 x 6.50-8, 6-ply rated, Premium tread	18 x 6.50-8, 6-ply rated, Premium tread
	Rear Tires	18 x 6.50-8, 6-ply rated, Premium tread	18 x 6.50-8, 6-ply rated, Premium tread
	Instrumentation	Battery capacity indicator, battery warning light	Battery capacity indicator, battery warning light
DIMENSIONS	Cargo Box Size	70.5" x 45.1" x 9.3" (17.1 ft³) 179.1 cm x 114.6 cm x 23.5 cm	70.5" x 45.1" x 9.3" (17.1 ft³) 179.1 cm x 114.6 cm x 23.5 cm
	Flat Bed Size	67.6" x 44.2" (171.8 cm x 112.2 cm)	67.6" x 44.2" (171.8 cm x 112.2 cm)
	Bed Height	27.0" (68.6 cm)	27.0" (68.6 cm)
	Bed Capacity	1000 lb. (499.4 kg)	1000 lb. (499.4 kg)
	Total Vehicle Capacity	1500 lb. (681.0 kg)	1500 lb. (681.0 kg)
	Overall Length	134.0" (340.4 cm)	134.0" (340.4 cm)
	Overall Width	49.3" (125.2cm)	49.3" (125.2 cm)
	Overall Height	48.0" (121.9 cm)	48.0" (121.9 cm)
	Wheelbase	98.5" (250.2 cm)	98.5" (250.2 cm)
	Ground Clearance Under Differential	4.5" (11.4 cm)	4.5" (11.4 cm)
	Fuel Tank Capacity	N/A	7.0 gallons (26.5 Liters)
	Tread	34.5"/38.5" (87.6 cm/97.8 cm)	34.5"/38.5" (87.6 cm/97.8 cm)
	Dry Weight Less Batteries	743 lb. (337.3 kg)	868 lb. (394.1 kg)
	Speed Range	5 - 17 mph (8-27.3 kph)	14 - 16 mph (22.5-25.7 kph)
	Outside Clearance Circle	24.7 ft. (7.5 m) dia.	24.7 ft. (7.5 m) dia.
	Turning Radius	12.0 ft. (3.7 m)	12.0 ft. (3.7 m)
	Intersecting Aisle Radius	90.0" (228.6 cm)	90.0" (228.6 cm)
	Vehicle Warranty	2-year limited*	2-year limited

*4-year, limited battery warranty for electric vehicles
**Exceeds SAE J1940 Performance Standards