



Close X

## Power Supply

**Power Source** Gas

Kawasaki 4-cycle, OHV, 286 cc, single cylinder, **Engine** 

air-cooled, pressure lubricated, spin-on oil filter

Horsepower

Automatic ground speed sensing, internally -Governor

geared in unitized transaxle

**Governed RPM** 2700 +/- 30

Ignition Electronic w/electronic RPM limiter

Unitized transaxle, helical gears: 11.8:1 DriveUnit

forward, 17.1:1 reverse

**Electrical** 12 volt, 500 cca 105 min. reserve

System

## Steering / Suspension

Steering Self-adjusting rack & pinion

Independent leaf spring with dual hydraulic

Suspension shocks

Rear Suspension Leaf springs with dual hydraulic shocks **Brakes** Self Adjusting Rear Mechanical Drum

Park Brake Foot-operated, multi-lock

Stabilizer Bar

## Frame / Chasis

Frame Chassis Aluminum I-Beam

Front Body ArmorFlex ®

**Body Finish** Matching paint over molded in color

Light Package

18 x 8.50-8, 4-ply rated, Premium tread **Tires Front Rear** 

Instrumentation Battery warning light

**Seating Capacity** 2 persons

**Overall Length** 91.5" (232 cm) **Overall Width** 47.25" (120 cm) **Overall Height** 69" (174 cm)

Wheelbase 65.5" (166.4 cm)

Ground

Clearance Under

4.5" (11.4 cm)

Differential

Braking 14 ft. (427 cm) Distance

**Fuel Tank** 

7 gallons (26.5 liters) Capacity

34.5"/38.5" (87.6 cm/97.8 cm) Tread

**Dry Weight Less** 

**Batteries** 

619 lb. (281 kg)

Forward Speed 12-15 mph (19.3-24.1 kph)

**Curb Clearance** 

Circle

17'6" ft. (5.3 m) dia.

**Turning Radius** 8'6" ft. (2.6 m) Vehicle Warranty Limited Lifetime Warranty of Fleet Golf Cars. See your Authorized Club Car representative for complete details and warranty information.