



EZ-GO RXV FREEDOM electric

Frame Welded steel with DuraShield™ epoxy coating
Body and Finish Injection Moulded TPO
Standard Colour Forest Green or Ivory
Power Source 48-volt DC
Motor Type 48-volt AC
Horsepower 3.3 kW continuous
Electric System 48-volt
Batteries (qty/type) Four, 12-volt deep cycle
Battery Charger Delta Q International Charger 80 VAC – 250 VAC 45-65 Hz CE approved
Speed Controller 235-amp AC controller
Drive Train Motor shaft direct drive
Transaxle Limited slip differential
Gear Selection Key switch
Rear Axle Ratio 16:99:1
Steering Double-ended rack and pinion
Front Suspension Independent A-Arm Coil over shock
Rear Suspension Mono-leaf spring w/hydraulic shocks
Service Brake Induction motor
Parking Brake Automatic electro-magnetic
Front Tyres Links 18 x 8.50-8 (4-ply rated)
Rear Tyres Links 18 x 8.50-8 (4-ply rated)
Seating Capacity 2-person
Dry Weight (without batteries) 259 kg
Curb Weight 417 kg
Vehicle Load Capacity 360 kg
Outside Clearance Circle 5.8 m
Ground Speed (level ground) 12-31 kph Programmable
Towing Capacity 3 golf cars with approved permanent tow bar
Overall Length 240 cm
Overall Width 119 cm
Overall Height (with canopy) 174 cm - top of sun canopy
Overall Height (no canopy) 116 cm - top of steering wheel
Ground Clearance (at differential) 11 cm
Wheel Base 167 cm
Front Wheel Track 90 cm
Rear Wheel Track 97 cm
Standard Features Split Windshield, State of charge meter, 48v World Charger, Gold Pinstripes, Fender Scuff Guards, Full diagnostic capability (with optional hand held unit)