

EZ-GO RXV FREEDOM gasoline

Frame Welded steel with DuraShield™ epoxy coating
Body and Finish Injection Moulded TPO
Standard Colour Forest Green or Ivory
Power Source 4 cycle 401cc low emissions
Valve Train Single cylinder OHV
Horsepower 9.7 kW exceeds SAE J1940 standard
Electric System Starter/generator, solid state regulator
Batteries (qty/type) One, 12-volt maintenance-free
Drive Train Automatic, continuously variable transmission (CVT)
Transaxle Differential with helical gears
Gear Selection Forward - reverse
Rear Axle Ratio 11:42:1 (forward) 15:78:1 (reverse)
Air Cleaner Remote intake, industrial-rated dry filter
Lubrication Pressurised oil system
Oil Filter Spin on
Cooling System Air cooled
Fuel Capacity 23.5 litres
Steering Double-ended rack and pinion
Front Suspension Independent A-Arm Coil over shock
Rear Suspension Mono-leaf spring w/hydraulic shocks
Service Brake Rear wheel mechanical, self-adjusting drums
Parking Brake Self compensating, single point engagement
Front Tyres Links 18 x 8.50-8 (4-ply rated)
Rear Tyres Links 18 x 8.50-8 (4-ply rated)
Seating Capacity 2-person
Curb Weight 339 kg
Vehicle Load Capacity 360 kg
Outside Clearance Circle 5.8 m
Ground Speed (level ground) 30 kph ± 0.8 kph
Towing Capacity 3 golf cars with approved permanent tow bar
Overall Length 240 cm
Overall Width 119 cm
Overall Height (with canopy) 174 cm - top of sun canopy
Overall Height (no canopy) 116 cm - top of steering wheel
Ground Clearance (at differential) 8 cm
Wheel Base 167 cm
Front Wheel Track 90 cm
Rear Wheel Track 97 cm
Standard Features Split Windshield, Met Gold Hub Cap, Fender Scuff Guards and Full diagnostic capability (with hand held diagnostic unit)
Other Standard Features Full diagnostic capability (hand held diagnostic unit), full torque, reduced speed reverse, energy transfer bumpers, sweater basket with individual sections, ergonomically designed console with four cup holders and integrated ball and tee holders, patented fold-down windscreen, suntop and standard gold wheel trims.