



EZ-GO TXT PDS

Frame Welded steel with DuraShield™ epoxy coating

Body and Finish Injection moulded TPO

Standard Colour Champagne or Hunter Green

Power Source 36-volt DC

Motor Type Shunt wound DC

Horsepower 1.9 kW continuous

Electric System 36-volt

Batteries (qty/type) Six, 6-volt deep cycle (115 minute minimum, 225 amp-hour @ 20 hr discharge rate)

Battery Charger 36v Delta Q World Charger 80 VAC – 250 VAC 45-65 Hz CE approved

Speed Controller Solid state continuously variable separately excited speed controller. Anti-roll back, walkaway™ braking and alarm. Regenerative 'Pedal Down' and/or 'Pedal Up' braking. Diagnostic mode 300 Amp capacity. Inductive throttle sensor. Full torque, reduced speed reverse.

Drive Train Motor shaft direct drive

Transaxle Differential with helical gears

Gear Selection Dash-mounted forward-neutral-reverse

Rear Axle Ratio 12:44:1

Steering Self-compensating single reduction rack and pinion

Front Suspension Leaf springs with hydraulic shock absorbers

Rear Suspension Leaf springs with hydraulic shock absorbers

Service Brake Dual rear wheel mechanical self-adjusting drum brakes

Parking Brake Self-compensating, single point engagement and automatic release

Front Tyres Links 18 x 8.50-8 (4-ply rated)

Rear Tyres Links 18 x 8.50-8 (4-ply rated)

Seating Capacity 2-person

Dry Weight (without batteries) 250 kg

Curb Weight 417 kg

Vehicle Load Capacity 360 kg

Outside Clearance Circle 5.8 m

Ground Speed (level ground) 19-24 kph

Towing Capacity 3 golf cars with approved permanent tow bar

Overall Length 231 cm

Overall Width 119 cm

Overall Height (with canopy) 173 cm - top of sun canopy

Overall Height (no canopy) 118 cm - top of steering wheel

Ground Clearance (at differential) 11 cm

Wheel Base 168 cm

Front Wheel Track 86 cm

Rear Wheel Track 97 cm

Standard Features Sun Top - Champ, Flat Windshield, Charge Meter, Hour Meter, 36v World Charger, Gold Spoke Hub Caps, Steep Hill Setting and Scuff Plates