



A Textron Company

EZ-GO MPT 1000E

Frame Welded steel with DuraShield™ powder coat
Front Body & Finish Injection molded Geloy XTW
Standard Colour Forest Green
Power Source 48 Volts DC
Motor Type Shunt Wound
Horsepower 1.9 kW @ 2700 rpm
Electric System 48 Volt
Batteries (qty/type) Eight, 6 Volt Deep Cycle
Battery Charger Delta Q International Charger 80 VAC – 250 VAC 45-65 Hz CE approved
Speed Controller 400 Amp Precision Drive System (PDS)
Drive Train Motor Shaft Direct Drive
Transaxle Differential with helical gears
Gear Selection Dash Mounted Forward-Neutral-Reverse
Rear Axle Ratio 14.7:1
Key or Pedal Start Pedal Start
Steering Self-compensating rack and pinion
Front Suspension Leaf springs with hydraulic shock absorbers
Rear Suspension Leaf springs with hydraulic shock absorbers
Service Brake Rear wheel mechanical self-adjusting drum
Parking Brake Self-compensating, single point engagement
Front Tyres Links 18 x 8.50 - 8 (4 Ply Rated)
Rear Tyres Turf Saver 18 x 8.50 - 8 (Load Range B)
Seating Capacity 2 Person
Dry Weight (without batteries) 370 kg
Curb Weight 590 kg
Bed Load Capacity 270 kg
Vehicle Load Capacity 450 kg
Outside Clearance Circle 6.7 m
Intersecting Aisle Clearance N/A
Ground Speed (level ground) 21 kph ± 0.8 kph
Towing Capacity 270 kg max load
Overall Length 280 cm
Overall Width 126 cm
Overall Height (with canopy) 173 cm
Overall Height (no canopy) 123 cm (Top of steering wheel)
Ground Clearance (at differential) 11 cm
Wheel Base 196 cm
Front Wheel Track 94 cm
Rear Wheel Track 97 cm
Cargo Box Material Roto-molded polyethylene
Cargo Box Capacity 0.27 m³
Cargo Box Length (inside) 91 cm
Cargo Box Width (inside) 112 cm
Cargo Box Depth (inside) 27 cm