

EZ-GO MPT 1200

Frame Welded steel with DuraShield™ powder coat

Front Body & Finish Injection molded Geloy XTW

Rear Body & Finish Steel. Base coat/clear coat

Standard Colour Forest Green

Power Source 4 Cycle 401 cc

Valve Train Single Cylinder OHV

Horsepower 9.7 kW Exceeds SAE J1940 Std.

Electric System Starter/Generator. Solid State Regulator

Batteries (qty/type) One, 12 Volt Maintenance Free

Drive Train Continuously variable transmission (CVT)

Transaxle Differential with helical gears

Gear Selection Forward - Reverse

Rear Axle Ratio 11.42:1 (Forward)

15.78:1 (Reverse)

Air Cleaner Replaceable Dry Cartridge

Lubrication Pressurized Oil System

Oil Filter Spin-On

Cooling System Air Cooled

Fuel Capacity 22.0 L tank

Key or Pedal Start Pedal Start

Steering Self-compensating rack and pinion

Front Suspension Leaf springs with hydraulic shock absorbers

Rear Suspension Leaf springs with hydraulic shock absorbers

Service Brake Rear wheel mechanical self-adjusting drum

Parking Brake Self-compensating, single point engagement

Front Tyres Links 18 x 8.50 - 8 (4 Ply Rated)

Rear Tyres Turf Saver 20 x 10.0 -10

Seating Capacity 2 Person

Dry Weight 360 kg

Curb Weight 380 kg

Bed Load Capacity 360 kg

Vehicle Load Capacity 545 kg

Outside Clearance Circle 6.7 m

Intersecting Aisle Clearance N/A

Ground Speed (level ground) 25.7 kph ± 0.8 kph

Towing Capacity 360 kg max load

Overall Length 280 cm

Overall Width 126 cm

Overall Height (with canopy) 173 cm

Overall Height (no canopy) 123 cm (Top of steering wheel)

Ground Clearance (at differential) 11 cm

Wheel Base 196 cm

Front Wheel Track 94 cm

Rear Wheel Track 97 cm

Cargo Box Material Roto-molded polyethylene

Cargo Box Capacity 0.27 m³

Cargo Box Length (inside) 91 cm

Cargo Box Width (inside) 112 cm

Cargo Box Depth (inside) 27 cm