



A Textron Company

EZ-GO MPT 800 electric

Frame Welded steel with DuraShield™ powder coat

Front Body & Finish Injection molded Gelay XTW

Rear Body & Finish Steel. Base coat/clear coat

Standard Colour Forest Green

Power Source 36 Volts DC

Motor Type Series Wound

Horsepower 1.9 kW @ 2700 rpm

Electric System 36 Volt

Batteries (qty/type) Six, 6 Volt Deep Cycle

Battery Charger Delta Q International Charger 80 VAC – 250 VAC 45-65 Hz CE approved

Speed Controller Solid State 300 Amp Rated

Drive Train Motor Shaft Direct Drive

Transaxle Differential with helical gears

Key or Pedal Start Pedal Start

Steering Self-compensating rack and pinion

Front Suspension Leaf springs with hydraulic shock absorbers

Rear Suspension Leaf springs with hydraulic shock absorbers

Service Brake Rear wheel mechanical self-adjusting drum

Parking Brake Self-compensating, single point engagement

Front Tyres Links 18 x 8.50 - 8 (4 Ply Rated)

Rear Tyres Turf Saver 18 x 8.50 - 8 (Load Range B)

Seating Capacity 2 Person

Dry Weight (without batteries) 310 kg

Curb Weight 470 kg

Bed Load Capacity 230 kg

Vehicle Load Capacity 360 kg

Outside Clearance Circle 5.76 m

Intersecting Aisle Clearance N/A

Ground Speed (level ground) 21 kph ± 0.8 kph

Towing Capacity 230 kg max load

Overall Length 262 cm

Overall Width 119 cm

Overall Height (with canopy) 173 cm

Overall Height (no canopy) 123 cm (Top of steering wheel)

Ground Clearance (at differential) 11 cm

Wheel Base 166 cm

Front Wheel Track 94 cm

Rear Wheel Track 97 cm

Cargo Box Material Roto-molded polyethylene

Cargo Box Capacity 0.17 m³

Cargo Box Length (inside) 77 cm

Cargo Box Width (inside) 113 cm

Cargo Box Depth (inside) 19 cm

Standard Features Charge Meter, Hour Meter, Front Bumper, Delta-Q 36V charger, Head and Tail Light, Mtr/Diff Scuff Guard & Tow hitch receiver