



A Textron Company

EZ-GO MPT 800 gasoline

Frame Welded steel with DuraShield™ powder coat
Front Body & Finish Injection molded Geloy XTW
Rear Body & Finish Steel. Base coat/clear coat
Standard Colour Forest Green
Power Source 4 Cycle 401 cc
Valve Train Single Cylinder OHV
Horsepower 9.7 kW Exceeds SAE J1940 Std.
Electric System Starter/Generator. Solid State Regulator
Batteries (qty/type) One, 12 Volt Maintenance Free
Drive Train Continuously variable transmission (CVT)
Transaxle Differential with helical gears
Gear Selection Forward - Reverse
Rear Axle Ratio 11.42:1 (Forward) 15.78:1 (Reverse)
Air Cleaner Industrial Rated Dry Filter
Lubrication Pressurized Oil System
Oil Filter Spin-On
Cooling System Air Cooled
Fuel Capacity 22.0 L tank
Key or Pedal Start Pedal Start
Steering Self-compensating rack and pinion
Front Suspension Leaf springs with hydraulic shock absorbers
Rear Suspension Leaf springs with hydraulic shock absorbers
Service Brake Rear wheel mechanical self-adjusting drum
Parking Brake Self-compensating, single point engagement
Front Tyres Links 18 x 8.50 - 8 (4 Ply Rated)
Rear Tyres Turf Saver 20 x 10 - 10 (Load Range B)
Seating Capacity 2 Person
Dry Weight 335 kg
Curb Weight 355 kg
Bed Load Capacity 230 kg
Vehicle Load Capacity 360 kg
Outside Clearance Circle 5.76 m
Intersecting Aisle Clearance N/A
Ground Speed (level ground) Fwd - 26.0 kph ± 0.8 kph Rev - 19.8 kph ± 0.8 kph
Towing Capacity 230 kg max load
Overall Length 262 cm
Overall Width 119 cm
Overall Height (with canopy) 173 cm
Overall Height (no canopy) 123 cm (Top of steering wheel)
Ground Clearance (at differential) 11 cm
Wheel Base 166 cm
Front Wheel Track 94 cm
Rear Wheel Track 97 cm
Cargo Box Material Roto-molded polyethylene
Cargo Box Capacity 0.17 m³
Cargo Box Length (inside) 77 cm
Cargo Box Width (inside) 113 cm
Cargo Box Depth (inside) 19 cm
Standard Features Fuel Gauge/Low Oil, Hour Meter, Front Bumper, Head and Tail Light, Eng/Diff Scuff Guard & Tow hitch receiver