



## **EZ-GO RXV Shuttle electric**

**Frame** Welded steel. DuraShield™ powder coat

**Body and Finish** Injection molded TPO

**Standard Colour** Forest Green

**Power Source** 48 Volts DC

**Motor Type** 48 Volt AC

**Horsepower** 3.3 kW Continuous

**Electric System** 48 Volt

**Batteries (qty/type)** Four, 12 Volt Deep Cycle

**Battery Charger** 48v Delta Q World Charger 80 VAC – 250 VAC 45-65 Hz CE approved

**Speed Controller** 235 Amp AC Controller

**Drive Train** Motor Shaft Direct Drive

**Transaxle** Limited Slip Differential

**Gear Selection** Dash Mounted Forward-Neutral-Reverse

**Rear Axle Ratio** 16.99:1

**Key or Pedal Start** Pedal Start

**Steering** Double Ended Rack & Pinion

**Front Suspension**

Independent A-Arm Coil over Shock

**Rear Suspension**

Mono-Leaf Spring With Hydraulic Shocks

**Service Brake** Induction Motor

**Parking Brake** Automatic Electro-Magnetic

**Front Tyres** Links 18 x 8.50 - 8 (4 Ply Rated)

**Rear Tyres** Links 18 x 8.50 - 8 (4 Ply Rated)

**Seating Capacity** 4 Person

**Dry Weight (without batteries)** 292 kg

**Curb Weight** 453 kg

**Vehicle Load Capacity** 325 kg

**Outside Clearance Circle** 5.8 m

**Intersecting Aisle Clearance** N/A

**Ground Speed (level ground)** 13 - 24 kph Programmable

**Towing Capacity** N/A

**Overall Length** 268 cm

**Overall Width** 119 cm

**Overall Height (with canopy)** 188 cm

**Overall Height (no canopy)** 116 cm

**Ground Clearance (at differential)** 11 cm

**Wheel Base** 167 cm

**Front Wheel Track** 90 cm

**Rear Wheel Track** 97 cm

**Standard Features** Canopy, Split Windshield, State of charge meter, 48v World Charger