



EZ-GO RXV Shuttle gasoline

Frame Welded steel. DuraShield™ powder coat
Body and Finish Injection molded TPO
Standard Colour Forest Green
Power Source 4 Cycle 401 cc Low Emission
Valve Train Single Cylinder OHV
Horsepower 9.7 kW Exceeds SAE J1940 Std.
Electric System Starter/Generator. Solid State Regulator
Batteries (qty/type) One, 12 Volt Maintenance Free
Drive Train Continuously variable transmission (CVT)
Transaxle Differential with helical gears
Gear Selection Forward - Reverse
Rear Axle Ratio 11.42:1 (Forward) 15.78:1 (Reverse)
Air Cleaner Industrial Rated Dry Filter
Lubrication Pressurised Oil System
Oil Filter Spin-On
Cooling System Air Cooled
Fuel Capacity 23.5 L tank
Key or Pedal Start Pedal Start
Steering Double Ended Rack & Pinion
Front Suspension Independent A-Arm Coil Over Shock
Rear Suspension Leaf springs with hydraulic shock absorbers
Service Brake Rear wheel mechanical self-adjusting drum
Parking Brake Self-compensating, single point engagement
Front Tyres Links 18 x 8.50 - 8 (4 Ply Rated)
Rear Tyres Links 18 x 8.50 - 8 (4 Ply Rated)
Seating Capacity 4 Person
Curb Weight 384 kg
Vehicle Load Capacity 325 kg
Outside Clearance Circle 5.8 m
Intersecting Aisle Clearance N/A
Ground Speed (level ground) 23 kph ± 0.8 kph
Towing Capacity N/A
Overall Length 268 cm
Overall Width 119 cm
Overall Height (with canopy) 188 cm
Overall Height (no canopy) 116 cm
Ground Clearance (at differential) 8 cm
Wheel Base 167 cm
Front Wheel Track 90 cm
Rear Wheel Track 97 cm
Standard Features Canopy, Split Windshield, Analog Fuel Gauge