



A Textron Company

EZ-GO ST 400 gasoline

Frame Welded steel. DuraShield™ powder coat
Front Body & Finish Injection Molded Geloy XTW
Rear Body & Finish Steel. Base coat/clear coat
Standard Colour Forest Green
Power Source 4 Cycle 401 cc
Valve Train Single Cylinder OHV
Horsepower 9.7 kW Exceeds SAE J1940 Std
Electric System Starter/Generator. Solid State Regulator
Batteries (qty/type) One, 12 Volt Maintenance Free
Drive Train Continuously variable transmission (CVT)
Transaxle Differential with helical gears
Gear Selection Forward - Reverse
Rear Axle Ratio 11.42:1 (Forward) 15.78:1 (Reverse)
Air Cleaner Replaceable Dry Cartridge
Lubrication Pressurised Oil System
Oil Filter Spin On
Cooling System Air Cooled
Fuel Capacity 22.0 L tank
Key or Pedal Start Pedal
Steering Self-compensating rack and pinion
Front Suspension Leaf springs with hydraulic shock absorbers
Rear Suspension Leaf springs with hydraulic shock absorbers
Service Brake Rear wheel mechanical self-adjusting drum
Parking Brake Self-compensating, single point engagement
Front Tyres Turf Saver 20 x 10 _10 (load range B)
Rear Tyres Turf Saver 20 x 10 _10 (load range B)
Seating Capacity 2 Persons
Dry Weight 410 kg
Curb Weight 430 kg
Bed Load Capacity 225 kg
Vehicle Load Capacity 360 kg
Outside Clearance Circle 6.7 m
Intersecting Aisle Clearance N/A
Ground Speed (level ground) 27.4 kph ± 0.8 kph
Towing Capacity 225 kg max load
Overall Length 283 cm
Overall Width 49.5 in
Overall Height (with canopy) 185 cm
Overall Height (no canopy) 126 cm Top of steering wheel
Ground Clearance (at differential) 15 cm
Wheel Base 77.0 in
Front Wheel Track 96 cm
Rear Wheel Track 97 cm
Cargo Box Material Roto-molded polyethylene
Cargo Box Capacity 0.27 m³
Cargo Box Length (inside) 91 cm
Cargo Box Width (inside) 112 cm
Cargo Box Depth (inside) 27 cm
Standard Features Hour Meter, Turf Tyres, Headlights w/ Taillights, Electric Dump Bed & Tow hitch receiver