

EZ-GO ST 480 gasoline

Frame Welded steel. DuraShield™ powder coat

Front Body & Finish Injection Molded Geloy XTW

Rear Body & Finish Steel. Base coat/clear coat

Standard Colour Forest Green

Power Source 4 cycle, 480 cc

Valve Train V Twin Cylinder OHV

Horsepower 11.9 kW rated

Electric System Starter/Generator. Solid State Regulator

Batteries (qty/type) One, 12 Volt Maintenance Free

Drive Train Continuously variable transmission (CVT)

Gear Selection Forward - Reverse

Rear Axle Ratio 13.32:1

Air Cleaner Dry cartridge w/permanent pre-filter/remote air

Lubrication Pressurised Oil System

Oil Filter Spin On

Cooling System Air Cooled

Fuel Capacity 22.0 L tank

Differential Helical gears with manual lock-up

Key or Pedal Start Pedal

Steering Self-compensating rack and pinion

Front Suspension Leaf springs with hydraulic shock absorbers

Rear Suspension Leaf springs with hydraulic shock absorbers

Service Brake Rear wheel mechanical self-adjusting drum

Parking Brake Hand operated

Front Tyres Turf Saver 20 x 10 _10 (load range B)

Rear Tyres Turf Saver 20 x 10 _10 (load range B)

Seating Capacity 2 Persons

Curb Weight 520 kg

Bed Load Capacity 225 kg

Vehicle Load Capacity 360 kg

Outside Clearance Circle 7.2 m

Intersecting Aisle Clearance N/A

Ground Speed (level ground) 25.7 kph ± 0.8 kph

Towing Capacity 225 kg max load

Overall Length 281 cm

Overall Width 127 cm

Overall Height (with canopy)

191 cm

Overall Height (no canopy) 125 cm (Top of steering wheel)

Ground Clearance (at differential) 15 cm

Wheel Base 77.0 in

Front Wheel Track 96 cm

Rear Wheel Track 97 cm

Cargo Box Material Roto-molded polyethylene

Cargo Box Capacity 0.27 m³

Cargo Box Length (inside) 91 cm

Cargo Box Width (inside) 112 cm

Cargo Box Depth (inside) 27 cm

Standard Features Hour Meter, Electric Dump Bed, Tow hitch receiver & Head and

Tail Lights