

EZ-GO TXT Shuttle 6 electric

Frame Welded steel. DuraShield™ powder coat
Body and Finish Injection molded TPO
Seat Pod Fibreglass & Gelcoat
Standard Colour Champagne
Power Source 48 Volts DC
Motor Type Shunt Wound
Intermittent Horsepower 13.5kw @1900 rpm
Continuous Horsepower 1.9kw
Electric System 48 Volt
Batteries (qty/type) Eight, 6 Volt Deep Cycle
Battery Charger 48 VDC Delta Q, 120/230 VAC, UL, CSA, CE
Speed Controller 400 Amp Precision Drive System (PDS)
Drive Train Motor Shaft Direct Drive
Transaxle Differential with helical gears
Gear Selection Dash Mounted Forward-Neutral-Reverse
Rear Axle Ratio 14.7:1
Key or Pedal Start Pedal Start
Steering Self-compensating rack and pinion
Front Suspension Leaf springs with hydraulic shock absorbers
Rear Suspension Leaf springs with hydraulic shock absorbers
Service Brake Rear wheel mechanical self-adjusting drum
Parking Brake Self-compensating, single point engagement
Front Tyres Links 18 x 8.50 - 8 (4 Ply Rated)
Rear Tyres Links 18 x 8.50 - 8 (4 Ply Rated)
Seating Capacity 6 Person
Dry Weight (without batteries) 320 kg
Curb Weight 540 kg
Vehicle Load Capacity 540 kg
Outside Clearance Circle 7.8 m
Ground Speed (level ground) 21 kph ± 0.8 kph
Towing Capacity N/A
Overall Length 338 cm
Overall Width 119 cm
Overall Height (with canopy) 183 cm
Overall Height (no canopy) 123 cm (Top of steering wheel)
Ground Clearance (at differential) 11 cm
Wheel Base 237 cm
Front Wheel Track 85 cm
Rear Wheel Track 97 cm
Standard Features Canopy, Screen, Hour Meter, Charge Meter, Delta-Q 48V charger & Head, Tail, Brake Lights