



A Textron Company

## **EZ-GO TXT Shuttle 6 gasoline**

**Frame** Welded steel. DuraShield™ powder coat  
**Front, Rear Body & Finish** Injection molded TPO  
**Seat Pod** Fibreglass & Gelcoat  
**Standard Colour** Champagne  
**Power Source** 4 Cycle 401 cc Low Emission  
**Valve Train** Single Cylinder OHV  
**Horsepower** 9.7 kW Exceeds SAE J1940 Std.  
**Electric System** Starter/Generator. Solid State Regulator  
**Batteries (qty/type)** One, 12 Volt Maintenance Free  
**Drive Train** Continuously variable transmission (CVT)  
**Transaxle** Differential with helical gears  
**Gear Selection** Forward - Reverse  
**Rear Axle Ratio** 11.42:1 (Forward) 15.78:1 (Reverse)  
**Air Cleaner** Industrial Rated Dry Filter  
**Lubrication** Pressurised Oil System  
**Oil Filter** Spin-On  
**Cooling System** Air Cooled  
**Fuel Capacity** 22.0 L tank  
**Key or Pedal Start** Pedal Start  
**Steering** Self-compensating reduction rack and pinion  
**Front Suspension** Leaf springs with hydraulic shock absorbers  
**Rear Suspension** Leaf springs with hydraulic shock absorbers  
**Service Brake** Rear wheel mechanical self-adjusting drum  
**Parking Brake** Self-compensating, single point engagement  
**Front Tyres** Links 18 x 8.50 - 8 (4 Ply Rated)  
**Rear Tyres** Links 18 x 8.50 - 8 (4 Ply Rated)  
**Seating Capacity** 6 Person  
**Curb Weight** 420 kg  
**Vehicle Load Capacity** 540 kg  
**Outside Clearance Circle** 7.8 m  
**Ground Speed (level ground)** 26 kph ± 0.8 kph  
**Towing Capacity** N/A  
**Overall Length** 338 cm  
**Overall Width** 119 cm  
**Overall Height (with canopy)** 183 cm  
**Overall Height (no canopy)** 123 cm (Top of steering wheel)  
**Ground Clearance (at differential)** 11 cm  
**Wheel Base** 237 cm  
**Front Wheel Track** 85 cm  
**Rear Wheel Track** 97 cm  
**Standard Features** Canopy, Screen, Hour Meter, Fuel Gauge/Low Oil & Head, Tail, Brake Lights